

Handy Electric Chamfering Tool

MINI BEVELER Model **EMB-0307B**



Double insulation




- Chamfering up to 3C stainless steel chamfering, and up to 7C mild steel chamfering.
- Carbide insert each with cutting edges on 4 sides.
- Chamfering angle can be adjusted to any desired position at 15° ~ 45°
- Pipe outer edge can be also chamfered with standard accessories that come with the tool.
- Dust box collects swarf and chips effectively.

Specifications

Model		EMB-0307B
Power Supply		220V ~ 240V AC, 50/60Hz
Rated Power Consumption	W	1010
Rated Current	A	4.6
Rated Duty		Continuous
Chamfering Capacity	Mild Steel	0C ~ 7C, 2R, 3R, 4R
	Stainless Steel	0C ~ 3C, 2R, 3R, 4R
Chamfer Angle		15° ~ 45°
Power Cord	m	4.0
Mass (Weight)	kg	3.9

Chamfer angle and width

Chamfer angle	Mild Steel (mm)			Stainless Steel (mm)		
	A	B	C	A	B	C
45°	7	7	9.9	3	3	4.2
30°	3.8	6.6	7.6	2.2	3.8	4.4
15°	1.5	5.6	5.8	1	3.8	3.9



Standard accessories

- Carbon Brush Ass'y : 1 set.
- 4 mm Hex. Wrench Key : 1 pc.
- Carbide Insert with Hole 12.7 : 1pc.
- Insert Set Screw 4 x 7 : 1 pc.
- Hex. Nut M8 : 2 pcs.
- 8 x 25 mm Hex. Socket Set Screw : 2 pcs.
- Spanner T-15D : 1 pc.

Handy Electric Chamfering Tool

MINI BEVELER

Model
MB-03A

 Double insulation



3C

2R, 3R

Compact and light for speed chamfering

- An outer R-part attachment allows chamfering of outer diameters with a radius greater than 170 mm.
- An optional inner head ass'y allows chamfering a pipe of inner diameter larger than 100 mm (50R).

Specifications

Model	MB-03A	
Power Supply (Single phase)	230V or 115V AC, 50/60 Hz	
Rated Power Consumption	W	430
Rated Current	A	2 / 4.5
Chamfering Capacity	0 - 3 C	
Chamfering Radius Capacity	2R, 3R	
Chamfer Angle	45°	
Rated Revolutions	min ⁻¹ (rpm)	7,100
Weight	kg	2.5

Standard accessories

- 3 & 4 mm Hex.Socket Screw Key : each 1 pc.
- Spanner T-9F: 1 pc.

Optional accessories

- TA9A386 Tip 9.525, 10 pcs./set
- TA9A592 Tip 9.525 2R, 10 pcs./set
- TA9A638 Tip 9.525 3R, 10 pcs./set
- TA9A594 Inner Head Ass'y